

Ficha Técnica

PINRODA PLAIN COATING



Descripción

Matt covering formulated using acrylic copolymers, pigments and gums, with a high level of resistance and fastness; with good resistance to the weather, to saltpetre and to abrasion, which gives it excellent results outdoors in moderately aggressive atmospheric environments.

Datos técnicos

Datos de identificación del producto

Color	White and others to order
Aspecto	Silk matt
Naturaleza	Acrylic copolymers
Peso específico	1.60 gr./cm ³

Datos de aplicación del producto

Rendimiento	4 - 6 m ² /kg.
Diluyente	Water



Repintado

After 4 hours.

Secado

30 minutes

Dónde aplicarlo

Brush, roller, spray gun.

For decorating and protecting exteriors, façades, yards, exterior walls, etc.

Modo de empleo

- On new surfaces that are clean, dry and free from rust, grease or saltpetre, if they are made of concrete or cement, apply directly, diluting by up to 20% for the first coat. If the surfaces are made of plaster, gypsum, etc. they must be sealed prior to application.
- On old painted surfaces in good condition, wash, sand to a smooth finish and then apply. If they are in poor condition, remove and proceed as per the instructions for new surfaces.

Formatos

Metal containers of: 3.5 Litres 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado

Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com