

# Ficha Técnica

## Satin Pinroda Acrylic Paint

Satin Pinroda Acrylic Paint

Versión: 09/05/2023



## Descripción

Acrylic Paint for Interior and Exterior. High quality, stability and resistance. Flawless and durable finish. Excellent whiteness and good coverage. Satin and silky finish. Very washable.

## Certificados de empresa



## Datos técnicos

### Datos de identificación del producto

Color

White



Aspecto	Satin
Naturaleza	Vinyl Copolymer Resins
Peso específico	1.31 gr./cm <sup>3</sup>

### Datos de aplicación del producto

Herramienta	Brush, Roller Spray Gun, Airless
Rendimiento	5 - 8 m <sup>2</sup> /Liters/Coat
Diluyente	Water
Repintado	6-7 hours
Secado	30 - 45 minutes

### Prestaciones finales

Resistencia al frote en húmedo	Class 2 UNE 13300 (>5.000 cycles, UNE 48243)
--------------------------------	--

## Dónde aplicarlo

In all types of surfaces, walls and ceilings, leaving a satin and silky finish, on surfaces smooth or rough (gotelé, pitted, scratched, etc.), and effective protection outdoors. The practical performance will depend on the thickness of the film, the nature of the substrate and the application method

## Productos relacionados

SELLACRYL  
THIXOTROPIC SYNTHETIC SEALER

## Modo de empleo

On new surfaces that are clean, dry and free from rust and grease made of:

- Cement and concrete: Directly, diluting by up to 25% for the first coat.
- Plaster, gypsums or wood: Sealing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With paints in good condition: Wash and sand to a smooth finish and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 7° C.
- Do not expose the containers to extreme temperatures.



## Almacenamiento

- In its original closed container, at not extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

## Formatos

Format: 3 & 15 Litres



*Atención al Cliente*

**967 44 05 96**

[atencionalcliente@jafep.com](mailto:atencionalcliente@jafep.com)



*Servicio Técnico*

**dpto\_tecnico@jafep.com**



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

[www.jafep.com](http://www.jafep.com)  
[jafep@jafep.com](mailto:jafep@jafep.com)