

Ficha Técnica

PINRODA TEXTURED COATING



Descripción

Textured petreous coating produced using resins in emulsion and pigments. It has a high level of resistance and fastness to light, which provides an elastic, water resistant finish but at the same time resistant to adverse climatological agents. It has excellent filling power, which conceals defects in mortar and excellent stippling, with a textured brilliant white finish. Easy to apply.

Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Copolymers in emulsion
Peso específico	1.70 gr./ cm

Datos de aplicación del producto

Rendimiento	1 m2/Kg. (varies depending on surface)
Diluyente	Water



Repintado

After 6 hours

Secado

30 minutes (touch dry)

Dónde aplicarlo

Petreous coating suitable for protecting façades, interior patios, in moderate climates

Modo de empleo

It can be applied by brush, roller or spray gun to create gotelé and tyrolean effects. The surfaces must be clean, dry and free from rust, saltpetre, damp, etc. If the surface is new it should be primed with a coat of paint diluted with 10-15% water, followed by an other coat to be applied neat in order to achieve the desired effect.

If the surface is old, and is already painted, you should try scraping and cleaning the parts which are in poor condition completely.

Do not apply below 5 °C.

Formatos

Metal containers of: 3.5 Litres 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA

DUBAI

ESPAÑA

MARRUECOS

POLONIA

UCRANIA



www.jafep.com
jafep@jafep.com