

Ficha Técnica

"R" SYNTHETIC PRIMER



Descripción

Quick drying satin synthetic primer for providing primary protection to iron and steel surfaces. Very good adhesion and resistance.

Datos técnicos

Datos de identificación del producto

Color	Rust Red, Grey and others to order
Aspecto	Satin
Naturaleza	Alkydic Resins
Peso específico	1.30 - 1.40 gr./cm ³ depending on colour.

Datos de aplicación del producto

Rendimiento	6 - 8 m ² /kg.
Diluyente	JAFEP Universal Solvent
Repintado	24 hours



Secado

15 minutes

Dónde aplicarlo

Essentially in a spray, airless spray.

For protecting both interior and exterior ferrous surfaces in the form of a first coat for subsequent finishing using industrial or decorative enamels.

Modo de empleo

Dilute the product as appropriate according to the application system and apply using thin coats on surfaces that have been degreased, with the rust removed, and that are clean and dry. If the surface is still rusty or the paintwork is in poor condition, the rust or paintwork should be removed by sanding or brushing.

Formatos

Metal containers of: 4 Litres; 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com