

Ficha Técnica

ROUGH EXTERIOR WALL



Descripción

Rough coating, matt and decorative finish, anti fracture and waterproof, produced using special acrylic resins as a base , which give it extraordinary elasticity and flexibility, even at extreme low temperatures, and a total waterproofing on vertical surfaces.

Datos técnicos

Datos de identificación del producto

Color	White and colours to order
Aspecto	Matt
Naturaleza	Acrylic
Peso específico	1,55 + 0,05 gr./cm 3 (at 23 +2°C)

Datos de aplicación del producto

Rendimiento	2 - 4 m2/Kg (by coat depending on surface)
Diluyente	Water



Secado

2 hours (approximately)

Dónde aplicarlo

Brush, roller or spray.

Productos relacionados

SELLACRYL

Modo de empleo

Product specifically designed to protect and waterproof exterior walls which require both elastic and structured finish because of fractures or future possible fractures.

On new surfaces that are clean, dry and free from rust, grease or saltpetre of cement and concrete: Apply directly but thin down to 50% with water for the first coat. Another effective primer would be SELLACRYL JAFEP, but thinning down with water in 1:3 proportion.

On painted surface in good condition and quality: wash, sand and apply directly or with a initial thinning down to 10-15%.

On painted surface in bad condition, remove and proceed like a new surface.

- Do not apply at temperatures below 5° C.

- Do not expose the packaging to extreme temperatures.

Formatos

Metallic packaging: 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado

Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com