

Ficha Técnica

WAX for MURALIA



Descripción

Muralia Wax is to be applied on Muralia Undercoating for obtain high decoration effects that evoke the old coating used in the rustic atmospheres.

“Muralia” Wax can be used straight from the can and offers a long usable time. It can be coloured by “Tinturas” colourants or using our Tinting Machine.

Datos técnicos

Datos de identificación del producto

Color	Transparent
Aspecto	Matt
Naturaleza	Acrylic copolymers
Peso específico	1.05 gr./cm ³

Datos de aplicación del producto

Rendimiento	18-20 m ² per can
Secado	6 - 8 hours



Dónde aplicarlo

Material gauze, cloth or sponge.
Muralla Wax is to be applied directly to Muralia Undercoating.

Modo de empleo

Ready for use. Muralia Wax is to be applied directly to Muralia Undercoating using with a rubbing motion.

Formatos

Plastic containers of: 750 mL.



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado

Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com