

Ficha Técnica

Waterproofing Anti-humidity Paint

Solvent acrylic paint

Versión: 22/08/2023



Descripción

Waterproofing coating against moisture on walls and ceilings, both indoors and outdoors, with great adherence, forming a layer that prevents or delays the passage of moisture.

Propiedades

- Great adhesion
- Prevents or delays the passage of moisture

Certificados de empresa



Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Acrylic Copolymers
Peso específico	1.40 gr./cm ³

Datos de aplicación del producto

Herramienta	Brush or Roller
Rendimiento	4 - 6 m ² /L(Coat
Diluyente	Jafep White Spirit
Repintado	6-8 hours
Secado	1 hour

Dónde aplicarlo

To apply both indoors and outdoors, in areas where there are humidity and saltpeter problems, it is not a finishing paint, once dry, it will be finished with a quality paint, plastic or enamel.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.

Modo de empleo

Thoroughly clean the affected area or that is considered the problem may occur, even scratching, if necessary. Then apply the Anti-Humidity Paint with a brush or roller, ensuring that it penetrates the treated surface.

Almacenamiento

- In its original closed container, at non-extreme temperatures and humidity.



- Keep away from direct sunlight.
- Recommended maximum since manufacture: 2 years.

Formatos

Container: 750 ml & 4L



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado
Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com