

Ficha Técnica

Aqua Polyurethane Varnish

Water-based polyurethane varnish

Versión: 22/08/2023



Ventajas

- High hardness
- High resistance to scratches and blows
- Excellent adhesion
- Very easy cleaning
- Fire resistance test: B-s1, d0

Descripción

Water-based polyurethane varnish specially formulated against abrasion, with high hardness and resistance to scratches and blows, therefore ideal for protecting wooden parquets, cork floors, stair treads, etc. It has high resistance to washing and is highly resistant to household products such as coffee, wine, oil...

Propiedades

Jafep Aqua Polyurethane Varnish protects the support as well as enhancing its aesthetic finish. Provides high hardness, resistance to rubbing and abrasion. It has high resistance to washing and excellent chemical resistance to food products (such as coffee, oil, alcohol, and other foods) as well as extraordinary resistance to water, leaving no marks after prolonged contact.

Certificados de empresa



Datos técnicos

Datos de identificación del producto

Color	Colorless
Aspecto	Gloss
Naturaleza	Polyurethane Aqueous Dispersion
Peso específico	1 + 0,05 gr/cm ³

Datos de aplicación del producto

Herramienta	Brush, Spray or Airless
Rendimiento	12-14 m ² /L/Coat
Diluyente	Thinner for water-based paints and enamels
Repintado	3 hours
Secado	30 minutes

Dónde aplicarlo

Its most interesting applications are: varnishing of wooden parquets, cork floors, stair treads, varnishing of furniture, doors, railings, etc. All this in interior application. It offers in all cases excellent hardness, chemical resistance, wear resistance and low odor.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current bottle with the next one at 50% to reduce the normal differences between batches.

Modo de empleo

- **NEW WOOD:** Sand thoroughly, clean and remove dust. Apply in thin coats, sanding lightly between coats.

- **VARNISHED WOOD:** Sand gently and clean any remaining dust and/or resin. Apply one or two coats undiluted. If it is in very poor condition, the existing varnish will be removed and the wood will be treated as new.



Almacenamiento

- In its original closed container, at non-extreme temperatures and humidity.
- Keep away from direct sunlight.
- Recommended maximum since manufacture: 2 years.

Formatos

Containers: 750 ml & 4L



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



ARGENTINA

DUBAI

ESPAÑA

MARRUECOS

POLONIA

UCRANIA



www.jafep.com
jafep@jafep.com