Ficha Técnica

Water Based Anti-Rust Primer





Ventajas

- Repaintable with all kinds of paints.
- Pleasant smell without toxic components.

Descripción

Anticorrosive primer based on specific pigments and special resins, with excellent adhesion and repaintable with all types of paints.

Free of toxic components and pleasant smell.

Propiedades

• Protection of iron and steel surfaces.

• Excellent adhesion.

Certificados de empresa



Datos técnicos

Datos de identificación del producto



Aspecto	Matt
Naturaleza	Modified Acrylic Emulsion
Peso específico	1,35 ± 0,05 gr/cm ³

Datos de aplicación del producto

Herramienta	Brush or Roller
Rendimiento	7 - 10 m²/L/Coat
Diluyente	Thinner for water-based paints and enamels
Repintado	5 hours
Secado	1 hour

5

Prestaciones finales

Resistencia al frote en húmedo

Dónde aplicarlo

Antirust protection of all types of iron and steel surfaces.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current bottle with the next one at 50% to reduce the normal differences between batches.

Modo de empleo

Stir the contents of the container well.

It is not recommended to dilute. Only if necessary, with the Thinner for water-based paints and enamels without exceeding 5%. Apply at low thicknesses of 25 -30 microns and at temperatures between 5 and 35 °C.

NEW SURFACES: Degrease, deoxidize and remove dust.



<u>REPAINT</u>: Sand and remove dust. If your condition is very bad, remove or even strip.

Almacenamiento

- In its original closed container, at non-extreme temperatures and humidity.
- Keep away from direct sunlight.
- Recommended maximum since manufacture: 2 years.

Formatos

Containers: 750 ml & 4L





