

Ficha Técnica

Easy Clean Emulsion Paint

Acrylic Emulsion Paint

Versión: 25/09/2023



Ventajas

- Ecological
- Anti absorbent
- Easy cleaning

Descripción

High quality emulsion paint, made with acrylic emulsion resins. With exceptional whiteness, coverage and performance. For perfect finishes both outdoors and indoors. Its most notable characteristic is minimal absorption, which combines with its magnificent washability, the ease of cleaning difficult stains (wine, coffee, etc.) with a damp cloth in just a few passes.

EasyClean meets all the ecological criteria for interior paints, which is why it has obtained the Community Ecological Label.

[¿Quiere saber más sobre la EcoLabel, la Etiqueta Ecológica Comunitaria?](#)

Propiedades

Paint with "EasyClean" technology that works by preventing the absorption of stains by the paint, leaving them on the surface so that they can be easily cleaned due to the excellent washability of the paint. It provides high-quality finishes and high covering power, presenting an unalterable matte white.

Certificados de producto



Certificados de empresa



Datos técnicos

Datos de identificación del producto

Color	White and colours upon request (Check tinting system´s Bases)
Aspecto	Matt
Naturaleza	Acrylic copolymers
Peso específico	1,45 ± 0.05 g/cm ³
Viscosidad	9,000 ± 1,500 cp (at Brookfield)

Datos de aplicación del producto

Herramienta	Brush, roller, spray gun or airless
Rendimiento	10 - 14 m ² /L/Coat
Diluyente	Thinner for water-based paints and enamels
Repintado	6 - 8 hours
Secado	45 minutes
Curado	28 days

Prestaciones finales

Resistencia al frote en húmedo

Class 1 (UNE-EN 13300 Standard); >10000 cycles (DIN 53778 Standard)

Dónde aplicarlo

On new cement, concrete, fiber cement surfaces, etc. and interiors of plaster, prefabricated, wood and metals suitably treated, such as: Sealer in wood and agglomerates; Primer on iron; Fixative primer on plaster and putties.

Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

Modo de empleo

ON NEW CLEAN, DRY AND FREE SURFACES OF RUST, GREASE OR SALITRE OF:

Cement and concrete: Once set. Directly, diluting up to 10% for the first layer.

Plaster, plaster or wood: Fixing or sealing previously with products appropriate to each case. Diluting up to 10% in the first coat.

ON OLD PAINTED SURFACES:

With paints in good quality condition: Wash and sand gently, putty if necessary and then apply.

With paints in poor condition: Remove and proceed as a new surface. If alkalinity is detected in the support, it must be corrected.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Containers: 4 & 15 L



Memoria descriptiva

On simple applications

The painting and/or decoration, especially indoors but also outdoors, of masonry surfaces will be carried out with Easy Clean Plastic Paint from the Pinturas Jafep company. The performance will be 10 to 14 m²/L and coat. The support must be clean, dry and free of rust, dust, grease, salt and moisture. The manufacturer's general recommendations will be respected.



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado

Compromiso Medioambiental y Social Jafep

