

Ficha Técnica

Aural Hogar Graphene Emulsion Paint

Matt Emulsion Paint

Versión: 22/09/2023



Ventajas

- Exceptional whiteness and coverage.
- Waterproofs while maintaining breathability.
- Anti-mold protection.
- High quality interior finishes.

Descripción

High quality emulsion paint, made with acrylic emulsion resins. With exceptional whiteness, coverage and performance. For perfect finishes both outdoors and indoors. Its composition includes preservative additives to protect the film and anti-mold preservative. Its particular pigmentation makes it recommended in high-quality interior finishes.

Propiedades

The Aural Hogar coating offers very high-coverage finishes of exceptional whiteness, which in addition to being perfect for outdoor use, thanks to the pigment additives used in its formulation, allows for very high quality interior finishes.

It has waterproofing properties, preventing water absorption, but at the same time allowing vapor transpiration, which allows air flow from the inside to the outside.

Certificados de empresa





Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Pure acrylic copolymers
Peso específico	1,50 ± 0,05 g/cm ³
Viscosidad	10,500 ± 1500 cp (at Brookfield)

Datos de aplicación del producto

Herramienta	Brush, roller, spray gun or airless
Rendimiento	10 - 15 m ² /L/Coat
Diluyente	Thinner for water-based paints and enamels
Repintado	6 - 8 hours
Secado	45 minutes
Curado	28 days

Prestaciones finales

Resistencia al frote en húmedo	Class 1 (UNE-EN 13300 Standard); >10000 cycles (DIN 53778 Standard)
Aspecto Aplicado	Matt

Dónde aplicarlo

On exterior surfaces with cement, concrete, fiber cement, etc. supports. and interiors of plaster, prefabricated, wood and suitably treated metals. All supports will be clean, dry, free of grease and saltpeter. Being a 100% acrylic product, it has great resistance to alkalis, which is why it is especially recommended in basements, cellars, garages, etc.



Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

Modo de empleo

ON NEW CLEAN, DRY AND FREE SURFACES OF RUST, GREASE OR SALITRE OF:

Cement and concrete: Once set. Directly, diluting up to 10-15% for the first layer. If it were very absorbent it would be set beforehand. If there are support defects, putty with a suitable product or on excessively polished surfaces, sand to open the pore.

Plaster, plaster or wood: Fixing or sealing previously with products appropriate to each case. Diluting up to 10% in the first coat.

ON OLD PAINTED SURFACES:

With paints in good quality condition: Wash and sand gently, putty if necessary and then apply.

With paints in poor condition: Remove and proceed as a new surface. If alkalinity is detected in the support, it must be corrected.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Containers: 750 ml, 4 & 15L

Memoria descriptiva

On simple applications

The cladding of the façade and other exterior vertical elements, as well as the painting and/or decoration inside, will be



carried out with Aural Hogar from the Jafep Painting company. The performance will be 10 to 15 m²/L and layer. The support must be clean, dry and free of rust, dust, grease, salt and moisture. The manufacturer's general recommendations will be respected.



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com