

Ficha Técnica

Esencial Supercubriente

Matt Emulsion Paint

Versión: 30/10/2023



Ventajas

- Extreme coverage
- Deodorized and flavored

Descripción

Matt emulsion paint based on acrylic resins in aqueous dispersion and pigments with high resistance and light fastness, used by professional painters in interiors and exteriors in a non-aggressive atmospheric environment.

Propiedades

Specially developed to achieve high coverage finishes and excellent performance with an optimal quality-price ratio.

It is suitable for interiors, but due to its formulation with pigments of high resistance and light fastness, it is also suitable for exteriors where the atmospheric environment is not too aggressive.

Reaction to fire classification B-s1,d0 according to UNE-EN 13501-1:2007 + A1:2010 standard (test carried out by Tecnalia).

Certificados de empresa





Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Acrylic Copolymers
Peso específico	1,60 ± 0.05 g/cm ³
Viscosidad	7,500 ± 1,000 cp (at Brookfield)

Datos de aplicación del producto

Imprimación	Sellacryl
Herramienta	Brush, roller, spray gun or airless
Rendimiento	7-9 m ² /L/Coat
Diluyente	Water
Repintado	2-4 hours
Secado	30 minutes
Curado	28 days

Prestaciones finales

Resistencia al frote en húmedo	Class 3 (UNE EN 13300) / 1,200 cycles (UNE EN 48243)
Aspecto Aplicado	Matt

Dónde aplicarlo

Suitable for the decoration and protection of unproblematic interior and exterior masonry surfaces.



100% Reciclado
Compromiso Medioambiental y Social Jafep



Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

Productos relacionados

Sellaprim Exterior use
THIXOTROPIC SYNTHETIC SEALER
Sellacryl Penetrating Acrylic Varnish and Fixer

Modo de empleo

ON NEW CLEAN, DRY AND FREE SURFACES OF RUST, GREASE OR SALITRE OF:

Cement and concrete: Once set. Directly, diluting up to 10% for the first layer.

Plaster, plaster or wood: Fixing or sealing previously with products appropriate to each case. Diluting up to 10% in the first coat.

ON OLD PAINTED SURFACES:

With paints in good quality condition: Wash and sand gently, putty if necessary and then apply.

With paints in poor condition: Remove and proceed as a new surface. If alkalinity is detected in the support, it must be corrected.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Containers: 750 ml, 4, 8 & 15 L



Memoria descriptiva

In simple applications

The painting and/or decoration, especially indoors but also outdoors in less aggressive conditions, of masonry surfaces will be carried out with the Essential Super-covering Plastic Paint from the Pinturas Jafep company. The performance will be 7 to 9 m²/L and layer. The support must be clean, dry and free of rust, dust, grease, salt and moisture. The manufacturer's general recommendations will be respected.



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com