# Ficha Técnica

# Nitrocellulose Lacquer

Alkyd Laquer

Versión: 30/10/2023





### Descripción

Colorless lacquer made from alkyd resins combined with plasticized nitrocellulose with a good balance of elasticity, adhesion and hardness.

## **Propiedades**

• Good elasticity, adhesion and toughness.

# Certificados de empresa

DUBAI



## **Datos técnicos**

ARGENTINA





#### Datos de identificación del producto

Color	Colorless
Aspecto	Satin, Gloss & Semi Matt
Naturaleza	Nitrocellulose resins combined with alkyds

#### Datos de aplicación del producto

Herramienta	Brush
Rendimiento	10-15 m <sup>2</sup> /L/Coat
Diluyente	Jafep Nitro Solvent
Repintado	24-48 hours
Secado	1 hour

#### Prestaciones finales

Resistencia al frote en húmedo

5

### Dónde aplicarlo

Protection and decoration of wooden surfaces, doors, windows, railings, etc. Interior

### **Precauciones**

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.

DUBAI

ESPAÑA

 Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

### Modo de empleo

ARGENTINA

- <u>NEW WOOD:</u> Clean, sand thoroughly and remove dust. Apply a first layer of Nitro Filler Primer which, once dry, will be sanded appropriately. Apply one or more undiluted coats as a finish.
- <u>VARNISHED WOOD:</u> It will be cleaned and sanded, if it is in good condition. If it were in very poor condition, all the existing varnish would be removed. It is advisable to do some compatibility testing with previous layers.





## **Almacenamiento**

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

### **Formatos**

Containers: 750 ml & 5 L







