Ficha Técnica

Gel Paint Remover





Descripción

Universal stripper that removes all types of old paints, enamels and varnishes quickly, comfortably, effectively and without dripping due to its gelatinous nature.

Propiedades

- For all types of paints.
- No drip.

Certificados de empresa



Datos técnicos

Datos de identificación del producto





Color	Reddish
Aspecto	Gel
Naturaleza	Cellulose type gel.

Datos de aplicación del producto

Herramienta	Brush
Rendimiento	4-7 m ² /L/Coat

Dónde aplicarlo

For the removal of a wide range of old paints, enamels and varnishes such as synthetic, cellulosic, greasy, emulsion, epoxy, etc., applied to metal and/or wood surfaces. On painted plastics, a prior test must be carried out since they can dissolve. They can even remove stone pastes. Very effective for cleaning brushes and rollers that are not rubber or nylon.

Precauciones

Do not use on rubber, plexiglass, linoleum, asphalt and most plastics.

Modo de empleo

Apply a generous and uniform layer with a natural bristle brush. Allow it to act on the old paint or varnish for the necessary time until the film softens (5 to 20 minutes), dissolves or peels off, removing it easily and comfortably using a scraper, metal or esparto brush, steel wool, etc.

Excessively dry or thick layers may require a second application, once the residue from the first has been removed.

Once the old gel-paint has been removed, clean the surface with water and detergent, or better with pure turpentine or a substitute for turpentine, benzine or alcohol. This cleaning is very necessary to achieve perfect adhesion of the new layers of paint to be applied.

Let the surface dry and it is ready to paint or varnish.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.





Formatos

Containers: 750 ml







