

Ficha Técnica

Telacril Transparent

Elastomeric waterproofing

Versión: 31/10/2023



Ventajas

- Transparent Property

Descripción

Acrylic, elastic and transparent varnish. Prepared to complement our line of Telacril waterproofing products, but in no case should it be considered a substitute for them. It provides acceptable elasticity and flexibility, waterproofing vertical supports, but above all it is characterized by its transparent property, which makes it ideal for waterproofing stone facades, exposed brick, etc.

Propiedades

- Highly elastic and highly resistant to weathering
- Ideal for exposed brick works
- With anti-mold preservative
- It has good elasticity and flexibility
- Elongation at break: 350%

Certificados de empresa



Datos técnicos

Datos de identificación del producto

Color	Transparent
Aspecto	Satin
Naturaleza	Acrylic copolymers in emulsion
Peso específico	1,05 gr/cm ³

Datos de aplicación del producto

Herramienta	Brush, roller, spray gun or airless
Rendimiento	6 - 8 m ² /L/Coat (variable depending on type and application)
Diluyente	Thinner for water-based paints and enamels
Repintado	7 hours
Secado	2-3 hours

Prestaciones finales

Resistencia al frote en húmedo	Clase 1 (según norma UNE-EN 13300); >10000 ciclos (según norma UNE-EN 48243)
--------------------------------	--

Dónde aplicarlo

Ideal for waterproofing stone facades, exposed brick, etc. To be used in specific applications where we seek, on the one hand, to avoid possible water leaks already detected or with microcracks, and on the other hand, to maintain the transparency of the support as much as possible, such as: Joints of transparent sheets of industrial roofs, mortars of aggregates, artificial stone and exposed brick facades, etc.

Product developed especially for vertical supports, it could also be used on horizontal ones with a certain slope, water can never remain stagnant nor can it be applied on completely horizontal supports.

Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.



- Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

Modo de empleo

Preparation of the support: the surfaces must be clean, dry and free of grease and saltpeter. Once prepared, it is recommended to apply a first coat diluted 1:1 in water as a primer. Subsequently, the necessary layers will be applied directly to use or with a slight dilution.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Containers: 750 ml, 4 & 15 L



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com

