Ficha Técnica

Veladuras Jafep (Glazed Paint)





Descripción

Water-based, acrylic product, low viscosity, very slow drying, to create patinas with various effects when applied on different backgrounds.

Certificados de empresa



Datos técnicos

Datos de identificación del producto

| Color | Colorless |
|------------|--------------------|
| Aspecto | Matt |
| Naturaleza | Acrylic copolymers |





Datos de aplicación del producto

| Rendimiento | 24 - 26 m ² /L/Coat |
|-------------|--|
| Diluyente | Thinner for water-based paints and enamels |
| Repintado | 12 - 24 hours |
| Secado | 6 - 8 hours |

Prestaciones finales

Resistencia al frote en húmedo

2

Dónde aplicarlo

Basically there are two lines of application:

- 1 On a granulated insulating undeecoat base
- 2 On a satin emulsion paint or water-based enamel. (Aural Satin or Acrimar Enamel)

Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

Modo de empleo

The use of different elements has given rise to different techniques, among which we can find:

Buffering: Dipping the tampon in the colored and very diluted product (50%) and discharge it. The surface is buffered, structuring the finish to taste.

Sponging: Prepared as before but giving slight turns of the wrist or small blows with the natural sponge.

Brushing: In this application with the brush we cross strokes or create circular effects.

Mopped. Suede Roller. And other techniques.





Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
 Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Containers: 750 ml







ARGENTINA

DUBAI

ESPAÑA

